Technical Information

SEALTITE BUILDING FASTENERS

Features and Benefits

ST PolyUrethane Strips

- Polyurethane foam strip is also referred to as Universal Closures.
- The material is a flexible semi-closed cell material that is used for filling voids & other openings between metal panels.
- They are available with or without pre applied adhesive.
- Standard length is 25'.



THICKNESS	WIDTH	LENGTH	ROLLS/BUNDLE
1"	1"	25 FT.	20/bundle
1"	1-1/2"	25 FT.	20/bundle
1-1/2"	1-1/2"	25 FT.	20/bundle
2"	2"	25 FT.	20/bundle

Features and Benefits

- TACKY TAPE is a 100% solids, asbestos free butyl tape sealant in roll form.
- Applications include metal roof endlaps, sidelaps, vents, gutters, pipe flashings, skylights.
- Service temperature range is -40 Degrees F-+180 Degrees F
- Material will not become brittle or crack.

TACKY TAPE ROLL	CARTON QTY.
3/32" x 3/8" x 45'	40
3/32" x 1/2" x 45'	32
3/32" x 3/4" x 45'	24
3/32" x 1" x 45'	20

ST Tacky Tape





6357 Reynolds Road Tyler, Texas 75708 | P.O. Box 4515, Tyler, Texas 75712 | 800-352-4864 | 903-592-2826 | 800-352-3940 Fax | 903-592-1583 Fax 9950 Princeton Glendale Rd. Cincinnati, OH 45246 | 800-944-8920 | 513-874-5905 | 800-944-4183 Fax | 513-874-5903 Fax